



General Overview

JackHammer Paint Gun Cleaner 6700 is part of the our "PureGreen" product line. "PureGreen" Products share the following environmentally enhancing attributes.

Pure Performance • Better Environment • Better Health & Safety
Designation of Bio-Based Items Rules • Meets USDA 7 CFR Part 2902
100% Biodegradable • USDA Bio-Preferred • 100% BioBased Renewables

About This Product

JackHammer Paint Gun Cleaner 6700 is a new class of "BioBased" paint gun cleaner It's unique properties will allow you to substitute Paint Gun Cleaner 6700 for your current petroleum-based cleaner. Although it is a powerful paint solvent it is also

very gentle to the environment & the health and safety of your employees. It's unique properties allow it to be used for a longer period of time thereby making it **very economical**. All of it's components are 100% Biodegradable & Renewable from natural resources. It is a natural, safe & effective alternative to your current solvent system.

- Quick Evaporating
- High Solvency
- Removes Most Polyurethanes, Enamels & Epoxies
- Leaves No Film

- Leaves No Film
- Longer Use per Gallon
- Excellent Shelf Life
- No Petroleum Distillates

Where To Use This Product

Use **JackHammer Paint Gun Cleaner 6700** wherever you are now using conventional solvent-cleaners. The following are suggested uses where this product will perform well. Call us with any questions you may have about this products many applications.

- IDEAL FOR FLUSHING PAINT LINES
- CLEANING PAINT GUNS & PAINT BOOTHS
- EXCELLENT PRE-PAINTING SURFACE CLEANER
- SPRAY, BRUSH MANUAL OR MACHINE APPLY

SUPERIOR PERFORMANCE IN PAINT GUN CLEANING SYSTEMS

Technical Information

JackHammer Paint Gun Cleaner 6700 contains 100% environmentally safe, renewable, readily biodegradable components. This product is designed to be part of a **"Green"** environmentally friendly maintenance program.

PHYSICAL PROPERTIES:

Appearance: Liquid
Odor: Mild Citrus
Boiling Point: >292° F
Solubility in Water: Insoluble
Ph: 7.3

Color: Clear-Water White

Evaporation Rate: 0.25

PRODUCT EFFECTIVENESS: The effectiveness of this product and the "speed" at which it works is determined by certain factors. In general these factors are as follows:

TEMPERATURE: The warmer the temperature, the faster this product will work.

The effective operating temperature is between $55^{\circ}\,\text{F.}$ & $120^{\circ}\,\text{F.}$

AGITATION: The use of an agitation with rag, brush or abrasive sponge speeds the process.

TYPE OF STAIN: Some paint & epoxy mixtures take longer than others.

It has been our experience that the "solvent" action of this product begins Immediately. The longer the product is allowed to remain on the contaminant, the better the result.

Packaging Information

2-1/2 GALLON "F STYLE JUGS" (2 per Case)
1 GALLON "F-STYLE JUGS" (4 per Case)
60 WET-WIPE "POP-UP" CONTAINERS
55 GALLON DRUMS
BULK PACKAGING AVAILABLE









